rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE




Quadro 2700K 25° 350mA CRI80 LED Einbaustr. 8W Weiß m.Konverter

Article nr.: ALU53471UWW

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector · housing color: white · 30° swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 900 lm · CRI: >80 · lifespan L70B50: >= 50,000 h · input: 350 mA DC · protection class III, MM · · installation depth: 35 mm · ceiling cut-out: 68 mm · outer dimmensions: 82 x 82 mm · including LED converter · this product contains a light source of energy efficiency class E

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094434711
Housing colour	Weiss
Length	82.00 mm
Width	82.00 mm
Height	25.00 mm
Hole size	68 mm
Depth in ceiling	35.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	900.00 lm



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



Quadro 2700K 25° 350mA CRI80 LED Einbaustr. 8W Weiß m.Konverter

Article nr.: ALU53471UWW

TECHNICAL DATA

Lamp	Inklusive LED
IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 80
Lifetime L70B50	50.000 h

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



Quadro 2700K 25° 350mA CRI80 LED Einbaustr. 8W Weiß m.Konverter

Article nr.: ALU53471UWW

TECHNICAL DRAWING

