



Quadro 2700K 25° 350mA CRI80 LED Einbaustr. 8W eisengeb.o.Konv. Article nr.: ALU53475UWWOK

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector · housing color: iron brushed · 30° swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 900 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III, MM · · installation depth: 35 mm · ceiling cut-out: 68 mm · outer dimensions: 82 x 82 mm · energie efficiency class: E · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094534756
Housing colour	Eisen-gebürstet
Length	82.00 mm
Width	82.00 mm
Height	25.00 mm
Hole size	68 mm
Depth in ceiling	35.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	900.00 lm






Quadro 2700K 25° 350mA CRI80 LED
Einbaustr. 8W eisengeb.o.Konv.
Article nr.: ALU53475UWWOK

TECHNICAL DATA

Lamp	Inklusive LED
IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h





Quadro 2700K 25° 350mA CRI80 LED
Einbaustr. 8W eisengeb.o.Konv.
Article nr.: ALU53475UWWOK

TECHNICAL DRAWING

