



**2700K 25° 350mA CRI90 m.Scheibe
LED Einbaustr. 8W eiseng. o.Konv.
Spannd.**

Article nr.: C57355UWWOK

stretch ceiling downlight · for indoor use, IP 20 · · housing: diecast aluminum, glass reflector, protection glass · housing color: iron brushed · 30° swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 670 lm · CRI: >90 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III · · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 87.8 mm · energy efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094973555
Housing colour	Eisen-gebürstet
Outer diameter	87 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	670.00 lm
Lamp	Inklusive LED
IP rating	20







2700K 25° 350mA CRI90 m.Scheibe
LED Einbaustr. 8W eiseng. o.Konv.
Spannd.

Article nr.: C57355UWWOK

TECHNICAL DATA

Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h





2700K 25° 350mA CRI90 m.Scheibe
LED Einbaustr. 8W eiseng. o.Konv.
Spannd.

Article nr.: C57355UWWOK

TECHNICAL DRAWING

