



ALUSPIEGEL 43° 350mA CRI90 LED-Modul 10W 2700K

Article nr.: 88809

LED-module 10W with reflector, MR16 · with LED Array Bridgelux (USA) · dimmable · · Input current: 350 mA · Power: 10W · Luminous flux: 838 lm · Light colour: 2700K · CRI: >80 · Lifetime L70B50: >= 50.000 h · Beamangle: 43° · protection class III · energy efficiency class: F · · Excellent heat dissipation due to optimised aluminium heatsink · Aluminium reflector with halogen appearance and uniform light distribution

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094888095
Length	70.00 mm
Outer diameter	50 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	838.00 lm
Lamp	Inklusive LED
IP rating	20
Power	10 W
Current mA	350 mA






ALUSPIEGEL 43° 350mA CRI90 LED- Modul 10W 2700K

Article nr.: 88809

TECHNICAL DATA

Amount of LED	1
Material	Aluminium
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h





**ALUSPIEGEL 43° 350mA CRI90 LED-
Modul 10W 2700K**
Article nr.: 88809

TECHNICAL DRAWING

